

Product Information



Perma-Chink® Log Home Sealant

- Provides a weather tight seal that helps insulate log homes.
- Excellent for new construction, restoration or repair of existing log homes.
- Remains flexible – follows log movement even in extreme climates.
- Authentic in appearance – looks like traditional mortar chinking.
- Ideal for do-it-yourself or commercial applications.
- Safe, easy to apply – water cleanup.

General Application Instructions

1. Apply over clean dry surfaces, free from oil, dirt or other foreign materials.
2. Apply only over “proper” backing or substrates. (See application guide for proper backer rod.)
For proper performance, cured material thickness should be no less than 1/4” and no more than 1/2”.

Tool Requirements:

Can be applied with caulking gun, application bag or high volume chink pump. You will also need a hand spray bottle for water and various sizes of trowels to finish Perma-Chink.

Application Methods:

1. Fill spray bottle with ordinary tap water.
2. Fill gun or bag with Perma-Chink. (Tie the large end of the bag with a string.)
3. Hold gun or bag firmly against backer surface; apply Perma-Chink so that it touches the surface of each log. (This may

require more than one bead of chinking.)

Once you have enough material to start trowelling, lightly spray it with water and trowel to achieve desired finish or texture.

Perma-Chink must be trowelled to each log to form a good seal. Any air pockets, or multiple beads that are present, must be trowelled out to help prevent blisters or depressions.

Special Instructions:

- Apply Perma-Chink 1/4” to 3/8” in thickness.
- Avoid application in direct sunlight
- Seam width should be 1/6 of log diameter.

Frequency:

One time application.

Packaging:

Perma-Chink is available in 11-oz. tubes, 30-oz. tubes and 5-gallon containers.

Shelf Life/Application Temperature:

Perma-Chink has a shelf life of 1 year. Application temperature is between 40° to 90°F.

Drying Time:

Perma-Chink skins over in 1 to 2 hours, cures in 2 to 8 weeks depending on temperature and humidity.

Color:

Available in eight colors.

The Log Home Care and
Maintenance Authority

Company Stores

Washington/Western
Division
1-800-548-1231

Tennessee/Eastern
Division
1-800-548-3554

Sevierville, TN
1-888-441-1116

Minnesota Branch
1-877-244-6548

Colorado Branch
1-800-433-8781

Montana Branch
1-800-479-7090

Stocking Distributors

Canadian Log Home
Supply, Canada
1-800-746-7773

Hess Log Home
Supplies, PA
1-800-257-4864

Log Home Center &
Supply, IN
1-800-773-6223

Steels Industrial
Products, Ltd., B.C.
1-877-846-7502

Timeless Wood Care
Products, MI
1-800-564-2987

visit us
online
www.permachink.com