

Acrylic™

1/07

GLOSS or SATIN

Durable Interior Finish

- Excellent for interior log walls, cabinets, paneling, timbers and trim.
- Highlights the beauty of stained or bare wood.
- Quick drying - tack free in approximately one hour.
- Protects latex stains or sealers from abrasion and wear.
- Resists yellowing.
- Water clean-up.
- Easy to apply.



Eastern Division 1-800-548-3554 Western Division 1-800-548-1231 Colorado 1-800-433-8781 Montana 1-800-479-7090 Minnesota 1-877-244-6548 Sevierville, TN 1-865-774-3307

STIR WELL BEFORE USING

Net Contents: 1 gallon (3.8 liters)

Acrylic™ Gloss / Satin Interior Finish

Acrylic Gloss or Satin is an excellent finish for highlighting interior log walls, cabinets, paneling, timbers, trim, railings and other vertical wood surfaces. The resilient acrylic polymers in Acrylic Gloss and Satin help protect water-based stains, paints and sealers from abrasion, wear and water damage. The smooth finish provided by Acrylic Gloss or Satin makes woodwork easier to clean.

Note: For floors and other horizontal wood surfaces we recommend the use of Sure Shine Interior Floor Finish.

Directions for Use

Surface Preparation: Surfaces should be clean, dry and free of all loose particles, dust, mold and mildew. If the surface is sealed or stained with LIFELINE Interior, less Acrylic Gloss or Satin will be required to obtain a smooth, bright finish. Do not use over recently applied oil-based finishes.

Coverage: One gallon of Acrylic Gloss or Satin will cover 350 to 450 square feet of hand-hewn logs or timbers or 450 to 600 square feet of smooth logs or millwork. Do not thin Acrylic Gloss or Satin with any solvent including water.

Application: Stir well before using. Apply an initial coat to previously sealed wood surfaces using a brush or airless sprayer. Immediately brush out runs and sags. If subsequent coats are desired, allow the first coat to completely dry and then lightly sand using 180 to 220 grit sandpaper. **Do not use steel wool or wire brushes!** Subsequent coats will not require sanding between coats.

Clean-up: Clean spills, tools and work area with clean water before the finish has dried.

Storage: Store Acrylic Gloss and Satin out of direct sunlight and protect from freezing. Although Acrylic Gloss and Satin are freeze-thaw stable, if the product is accidentally frozen, allow to thaw and check for suitability of use before applying.

LIMITED WARRANTY

Perma-Chink Systems, Inc. warrants and represents that PERMA-CHINK LOG HOME PRODUCTS will conform to the description and specifications previously set forth and be free from defects in material and workmanship when shipped to the buyer. EXCEPT WHEN HEREIN EXPRESSLY STATED, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, APPLICABLE TO THIS PRODUCT. PERMA-CHINK SYSTEMS EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

CAUTIONS: DO NOT TAKE INTERNALLY. IF SWALLOWED, DRINK MILK. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY SEALED AFTER EACH USE. USE IN WELL VENTILATED AREA. DO NOT INHALE VAPORS. WEAR EYE PROTECTION WHILE USING.



Eastern Division 1-800-548-3554
Western Division 1-800-548-1231
Colorado 1-800-433-8781
Minnesota 1-877-244-6548
Montana 1-800-479-7090
Sevierville, TN 1-865-774-3307

1/07